

**Prompter Selection Guide**  
877-TEKSKIL  
Tekskil.com



Specifications	10R Prompter	15R Prompter	15PR Prompter	17R Prompter	17PR Prompter
Brightness (cd/m <sup>2</sup> )	1200	600	1200	600	1200
Contrast Ratio	1000	600	1000	600	1000
Power Consumption (12 VDC)	18 Watts	32 Watts	24 Watts	35 Watts	28 Watts
Panel Weight	4.5 lbs.	7 lbs.	7 lbs.	9 lbs.	9 lbs.
Warranty	5 Years	1 Year	5 Years	1 Year	5 Years
<b>Beamsplitter Size</b>					
Standard 4:3 lens	✓	--	--	--	--
Standard 16:9 HD lens	✓	✓	✓	✓	✓
Wide Angle 16:9 HD lens	✓	✓	✓	✓	✓
<b>Tally Option</b>					
Front mount single-stage LED cluster	✓	✓	✓	✓	✓
Top mount dual-stage LED bars & CAM #	--	✓	✓	✓	✓
<b>Timing Option</b>					
6 digit VITC SMPTE clock, 2.3" high LEDs	--	✓	✓	✓	✓

- Tekskil Displays feature:
- Sophisticated power management to prevent image distortion, electrical noise and display damage
  - Signal conditioning to eliminate ground loops and drop-outs
  - Temperature control elements, including twin cooling fans to prevent image loss, back light failure and circuitry overheats
- Tekskil Prompting Systems feature:
- Integrated stabilization and dampening elements to minimize vibration and lurching during camera movement
  - Micro-truss construction provides optimal strength, balance and weight for **greatly** reduced pan/tilt servo stress and failure